



## Istruzioni di montaggio

Assembly instructions  
Instructions de montage  
Montageanleitung  
Instrucciones de montaje



1



2



3



4



5



6

WWW.TETRAX.COM

MADE IN ITALY



## Assembly instructions

- Clear the rear device surface with a damp cloth or paper and dry;
- Take the clip and place it on Tetrax<sup>®</sup>, leaving the adhesive part free (photo 1, photo 2);
- Remove the clip adhesive film;
- Use the blister as a Template to find the centre of the device in a smooth area, being careful to place it in the upper half of the device (photo 3);
- Adequately press the Tetrax against the device for about 10 seconds so that the clip 3M adhesive perfectly adheres to the surface (photo 3);
- Remove Tetrax and make sure the clip is well-adhered to the device (photo 4);
- EGO-GEO version: place Tetrax<sup>®</sup> on the car vent, turning the ring until the clamps are adequately tightened, without forcing (photo 5);
- FIX version: apply Tetrax<sup>®</sup> after removing the adhesive film on a flat and smooth surface and slightly press down for about 10 seconds so that the 3M adhesive perfectly adheres to the surface (photo 5);
- Near the Tetrax<sup>®</sup> device clip, the four magnets' force of attraction will do the rest (photo 6).
- To remove the device, slide it sideways or down.

## Warnings

- Do not assemble or adjust Tetrax while driving;
- Due to its size, it is not suitable for children under 5;
- Do not use for purposes other than those intended;
- Roughness or surface wrinkles may alter clip adhesion;
- Magnetic device: do not leave credit cards or other magnetic storage supports near Tetrax since saved information may be cancelled;
- WARNING: particularly critical driving situations (i.e.: off-road or on particularly uneven roads), may compromise good Tetrax operations.

Maximum load capacity: 150 gr.

Warranty: 24 months

MADE IN ITALY